



Text for Invitation to Tender ABS-Lock® DH04 System:

Roof Safety Hook in accordance with EN 795 A+B and 517 B

Roof safety hook manufactured completely from stainless steel for usage as an anchorage point for personal protective equipment kits. Licensed for 3 individuals. Installed using special screws capable of safely dispersing loads in any direction (including the apex and roof verge). Supply and installation of the DH04 on the rafters (min. 60x120mm). Can be installed through lateral or counter battens, with or without rafter insulation.

The rafter insulation thickness is required = _____ mm

<u>Pos.</u>	<u>Description</u>	<u>Quantity</u>	<u>PPU</u>	<u>Total</u>
	ABS-Lock® DH04	_____	_____	_____ €

PPE set, CE-tested, consisting of:

Safety cable ABS ASK 8, 14mm x 23m sharp edge-protected kernmantle cable with 2 freely-moving carabiner hooks and rope shortener designed for hooking onto ABS-Lock® DH 04 roof anchorage points.

Connector cable up to _____ m in length, including a rope shortener and force absorber, designed for work carried out near precipitous edges

Safety harness, protective bag

<u>Pos.</u>	<u>Description</u>	<u>Quantity</u>	<u>PPU</u>	<u>Total</u>
	ABS PPE Set	_____	_____	_____ €
	ABS ASK 8	_____	_____	_____ €

ABS Safety GmbH

Gewerbering 3

47623 Kevelaer

Germany

Tel.: 0049 (0) 2832 97281-0

Fax: 0049 (0) 2832 97281-29

info@fall-arrest.eu

www.fall-arrest.eu